

Pointed combination pliers, chrome-plated, insulated, 145 mm



Small power combination pliers with pointed jaws... For all common installation and repair work... particularly handy: ideal for working in hard-to-reach areas thanks to slim head shape with tapered jaws (very twist-proof). Gripping surface convex on one side - for secure gripping of flat parts. milled groove in the gripping area enables secure holding and pulling of small workpieces such as nails, pins and bolts. The reliable and versatile combination pliers: for on the go. Easy cutting thanks to high transmission power joint. With cutting edges for soft, medium-hard and hard wire. Cutting edges additionally induction hardened, cutting edge hardness approx. 61 HRC. Long durability and stable tips.

- Cutting values medium-hard wire (diameter): Ø 3.0mm
- Cutting values hard wire (diameter): Ø 2.0mm
- Cutting value Cu-cable, stranded: Ø 8.0mm
- Cutting value Cu-cable, stranded: 16.0mm²
- VDE-tested: Yes

- The reliable and versatile combination pliers for on the go
- Easy cutting thanks to high transmission power joint
- With cutting edges for soft, medium-hard and hard wire
- Cutting edges additionally induction hardened, cutting edge hardness approx. 61 HRC
- Long durability and stable tips

Item no.	WL61303
Model	08 26 145
Manufacturer	KNIPEX
Manufacturer article no.	08 26 145
GPSR manufacturer data	KNIPEX-Werk

Oberkamper Strasse 13
DE-42349 Wuppertal-Cronenberg
www.knipex.de

Length	156 mm
Width	58 mm
Height	18 mm
Length with packaging	177 mm
Width with packaging	61 mm
Height with packaging	30 mm
Volume with packaging	0.315 dm ³
Sales unit	1 piece
Content unit	1 piece
Type of packaging	single pack
Incl. battery	no
Standards	DIN EN 60900, DIN ISO 5746 IEC 60900
RoHS compliant	no
Surface	chrome-plated
VDE	yes
ESD compliant	no
Fastening for fall protection	nein
Tool length	145 mm
Description Head	Chrome-plated
Grip (expression)	VDE insulated with multi-component sleeves, VDE-tested
Cutting value copper cable, stranded	16 mm ²
Cutting value copper cable, stranded (diameter)	8 mm
Cutting value wire diameter (hard)	2 mm
Cutting value wire diameter (medium)	3 mm
Type of pliers	combination pliers

Other versions

Item no.	Fastening for fall protection
WL61302	ja
WL61303	nein