Electrical installation pliers, chrome-plated, insulated, fixing lug, 200 mm



6 functions in one pair of pliers. Multifunctional pliers for electrical installations; for gripping flat and round material, bending, deburring, cable cutting, stripping and crimping wire-end ferrules. Smooth gripping surfaces at the tip for damage-free gripping of single wires; profiled gripping surfaces and burner hole for gripping flat and round material. Distinctive outer edge on the gripping surfaces for working on flush-mounted boxes and deburring feed-through holes. Stripping holes for conductors 0.75 - 1.5 mm^2 and 2.5 mm^2. Crimping nest for wire end ferrules 0.5 - 2.5 mm^2. Cable shears with precision cutting edges (inductively hardened) for Cu and Al cables up to 5 x 2.5 mm^2 / Ø 15 mm. Slim design for good accessibility. Bolted joint: precise, backlash-free operation of the pliers. Pliers with integrated insulated fastening eye for attaching a fall protection. - Cutting value Cu-cable, stranded: Ø 15mm - Cutting value Cu-cable, stranded: 50mm^2 - Stripping values for single wires: 0.75 - 1.5mm^2 / 2.5mm^2 - Capacity square millimetre: 0.5 - 2.5mm^2 - AWG: 1 / 0 - Fall protection: Yes - VDE-tested: Yes

- Smooth gripping surfaces at the tip for damage-free gripping of single wires
- Profiled gripping surfaces and burner hole for gripping flat and round material
- Distinctive outer edge on the gripping surfaces for working on flush-mounted boxes and deburring feed-through holes
- Stripping holes for conductors 0.75 - 1.5 mm^2 and 2.5 mm^2
- Crimping nest for wire end ferrules 0.5 - 2.5 mm^2
- Cable shears with precision cutting edges (inductively hardened) for Cu and Al cables up to 5 x 2.5 mm^2 / Ø 15 mm
- Slim design for good accessibility
- screwed joint: precise, backlash-free operation of the pliers

Item no.	WL61360
Model	13 96 200 T
Manufacturer	KNIPEX
Manufacturer article no.	13 96 200 T
GPSR manufacturer data	KNIPEX-Werk Oberkamper Strasse 13 DE-42349 Wuppertal-Cronenberg www.knipex.de
Length	210 mm
Width	63 mm
Height	28 mm
Length with packaging	211 mm
Width with packaging	66 mm
Height with packaging	31 mm
Volume with packaging	0.42 dm^3
Sales unit	1 piece
Content unit	1 piece
Type of packaging	single pack
Standards	DIN EN 60900 | IEC 60900
RoHS compliant	no
Surface	chrome-plated
VDE	yes
ESD compliant	no
Fastening for fall protection	ja
Jaw shape	flat
AWG	1 / 0
Crimp profile	Mandrel crimp
Stripping value in mm^2	0.75 – 2.5 mm^2
Tool length	200 mm
Description Head	chrome-plated
Grip (expression)	VDE, Tethered Tools | insulated with multi-component sleeves, VDE-tested; with integrated insulated fastening eye for attaching a fall protection device
Cutting value copper cable, stranded	50 mm^2
Cutting value copper cable, stranded (diameter)	15 mm
Type of pliers	electronic pliers

Other versions

Item no.	Fastening for fall protection
WL61360	**ja**
WL61361	nein