

## Bolt end cutter, high gear ratio, black atramentized, 200 mm



Bolt end cutter powerful, compact, comfortable. Compared to conventional lever end cutters, larger capacity with lower power requirement and better handling. With cutting edges for soft and hard wire as well as piano wire. Particularly high cutting capacity with low power requirement due to optimum transmission ratio. Cutting edges additionally induction hardened, cutting edge hardness approx. 64 HRC. Forged. - Cutting values soft wire (diameter): Ø 1 - 6mm - Cutting values medium-hard wire (diameter): Ø 4,0mm - Cutting values hard wire (diameter): Ø 3,5mm - Cutting values piano wire (diameter): Ø 3,0mm

- Compared to conventional lever end cutters larger capacity with lower power requirement and better handling
- With cutting edges for soft and hard wire as well as piano wire
- Particularly high cutting capacity with lower power requirement due to optimum transmission ratio
- Cutting edges additionally induction hardened, cutting edge hardness approx. 64 HRC
- Forged

Item no.	<b>WL61611</b>
Model	61 01 200
Manufacturer	KNIPEX
Manufacturer article no.	61 01 200
GPSR manufacturer data	KNIPEX-Werk Oberkamper Strasse 13 DE-42349 Wuppertal-Cronenberg www.knipex.de
Length	220 mm
Width	45 mm

Products for the electronic industry



Height	15 mm
Length with packaging	237 mm
Width with packaging	67 mm
Height with packaging	35 mm
Volume with packaging	0.535 dm <sup>3</sup>
Sales unit	1 piece
Content unit	1 piece
Type of packaging	single pack
RoHS compliant	no
Surface	black atramentised
VDE	no
Jaw angle	Jaws, angled, 5
ESD compliant	no
Tool length	200 mm
Type of side cutters	end cutter
Description Head	polished
Grip (expression)	Covered with plastic
Cutting value wire diameter (hard)	3.5 mm
Cutting value wire diameter (medium)	4 mm
Cutting value wire diameter (soft)	1.6 mm
Type of pliers	cutting pliers