

Power end cutter, black atramentized, 160 mm



With cutting edges for soft and hard wire as well as piano wire. High cutting performance with less effort due to optimum coordination of cutting edge angle and transmission ratio. Cutting edges additionally induction hardened, cutting edge hardness approx. 64 HRC. - Cutting values soft wire (diameter): Ø 4.5mm - Cutting values medium-hard wire (diameter): Ø 3.4mm - Cutting values hard wire (diameter): Ø 2.5mm - Cutting values piano wire (diameter): Ø 2.0mm

- With cutting edges for soft and hard wire as well as piano wire
- High cutting performance with less effort due to optimum coordination of cutting edge angle and transmission ratio
- Cutting edges additionally induction hardened, cutting edge hardness approx. 64 HRC

Item no.	WL61624
Model	67 01 160
Manufacturer	KNIPEX
Manufacturer article no.	67 01 160
GPSR manufacturer data	KNIPEX-Werk Oberkamper Strasse 13 DE-42349 Wuppertal-Cronenberg www.knipex.de
Length	165 mm
Width	52 mm
Height	16 mm
Length with packaging	213 mm
Width with packaging	75 mm
Height with packaging	49 mm
Volume with packaging	0.783 dm ³
Sales unit	1 piece

Products for the electronic industry



Content unit	1 piece
Type of packaging	single pack
Incl. battery	no
Standards	DIN ISO 5748
RoHS compliant	no
Surface	black atramentised
VDE	no
ESD compliant	no
Tool length	160 mm
Type of side cutters	end cutter
Description Head	polished
Grip (expression)	coated with plastic
Cutting value wire diameter (hard)	2.5 mm
Cutting value wire diameter (medium)	3.4 mm
Cutting value wire diameter (soft)	4.5 mm

Other versions

Item no.	Tool length
WL30647	140 mm
WL61624	160 mm
WL61625	200 mm