

Power end cutter, black atramentized, 200 mm



With cutting edges for soft and hard wire as well as piano wire. High cutting performance with less effort due to optimum coordination of cutting edge angle and transmission ratio. Cutting edges additionally induction hardened, cutting edge hardness approx. 64 HRC. - Cutting values soft wire (diameter): Ø 5mm - Cutting values medium-hard wire (diameter): Ø 3,8mm - Cutting values hard wire (diameter): Ø 3,0mm - Cutting values piano wire (diameter): Ø 2,5mm

- With cutting edges for soft and hard wire as well as piano wire
- High cutting performance with less effort due to optimum coordination of cutting edge angle and transmission ratio
- Cutting edges additionally induction hardened, cutting edge hardness approx. 64 HRC

Item no.	WL61625
Model	67 01 200
Manufacturer	KNIPEX
Manufacturer article no.	67 01 200
GPSR manufacturer data	KNIPEX-Werk Oberkamper Strasse 13 DE-42349 Wuppertal-Cronenberg www.knipex.de
Length	250 mm
Width	50 mm
Height	16 mm
Length with packaging	236 mm
Width with packaging	88 mm
Height with packaging	52 mm
Volume with packaging	1.104 dm ³
Sales unit	1 piece

Products for the electronic industry



Content unit	1 piece
Type of packaging	single pack
Standards	DIN ISO 5748
RoHS compliant	no
Surface	black atramentised
VDE	no
ESD compliant	no
Tool length	200 mm
Type of side cutters	end cutter
Description Head	polished
Grip (expression)	Covered with plastic
Cutting value wire diameter (hard)	3 mm
Cutting value wire diameter (medium)	3.8 mm
Cutting value wire diameter (soft)	5 mm

Other versions

Item no.	Tool length
WL30647	140 mm
WL61624	160 mm
WL61625	200 mm