

Power side cutter, black atramentized, 140 mm



For the hardest, permanent use. High cutting performance with low effort due to optimum coordination of cutting edge angle and transmission ratio. Precision cutting edges additionally induction hardened, (cutting edge hardness approx. 64 HRC) for all wire types including piano wire. - Shape: 0 - Cutting values medium-hard wire (diameter): Ø 3.1mm - Cutting values hard wire (diameter): Ø 2.0mm - Cutting values piano wire (diameter): Ø 1.5mm

- For the hardest, permanent use
- High cutting performance with low effort due to optimum coordination of cutting edge angle and transmission ratio
- Precision cutting edges additionally induction hardened, (cutting edge hardness approx. 64 HRC) for all wire types including piano wire

item number	WL61687
model	74 02 140
manufacturer	KNIPEX
manufacturer item number	74 02 140
GPSR manufacturer information	KNIPEX-Werk Oberkamper Strasse 13 DE-42349 Wuppertal-Cronenberg www.knipex.de
length	145 mm
width	48 mm

Products for the electronic industry



height	20 mm
length with packaging	230 mm
width with packaging	83 mm
height with packaging	48 mm
Packaging volume	0.924 dm ³
order unit	1 piece
content unit	1 piece
type of packaging	single pack
standards	DIN ISO 5749
RoHS conform	no
surface	black atramentised
VDE	no
ESD safe	no
tether attachment point	nein
tool length	140 mm
type of side cutter	side cutter
description head	polished
type of handle	with multi-component handles
cutting value wire diameter hard	2 mm
cutting value wire diameter medium	3.1 mm

Other versions

item number	tool length	tether attachment point
WL61687	140 mm	nein
WL61688	160 mm	nein
WL61689	180 mm	nein
WL13356	200 mm	nein
WL61692	250 mm	nein