Precision electronics side cutter, burnished, 125 mm



Precision pliers for the finest cutting work, e.g. in electronics and precision mechanics. Very precisely ground, sharp cutting edges with very small facets for exact cuts on sensitive electronic components; also available without facet for flush cutting. Cutting edges additionally induction hardened, cutting edge hardness approx. 64 HRC. Approx. 20 % less weight than conventional electronic pliers. Bolted joint with particularly carefully manufactured joint surfaces for uniform, low-friction movement in the entire opening range. Smooth-running double spring for smooth and even opening. Ergonomically optimised multi-component sleeves. round head. all edges on the head rounded - reduces the risk of insulation damage when correcting wiring harnesses. - Shape: 0 - cutting values medium hard wire (diameter): Ø 1,3mm - cutting values hard wire (diameter): Ø 0,7mm - cutting values soft wire (diameter): Ø 0,2 - 1,7mm - jaw length (B): 10mm - jaw thickness (at joint) (D): 6,5mm - head width (A): 11mm

- Precision pliers for finest cutting work, e.g. in electronics and precision mechanics
- Very precisely ground, sharp cutting edges with very small facets for exact cuts on sensitive electronic components
- Also without facet for flush cutting
- Cutting edges additionally induction hardened, cutting edge hardness approx. 64 HRC
- Approx. 20 % less weight than conventional electronic pliers
- Bolted joint with particularly carefully manufactured joint surfaces for uniform, low-friction movement in the entire opening range
- Smooth-running double spring for smooth and even opening
- Ergonomically optimised multi-component handles

Item no.	WL61730
Model	79 02 125 S1
Manufacturer	KNIPEX
Manufacturer article no.	79 02 125 S1
GPSR manufacturer data	KNIPEX-Werk Oberkamper Strasse 13 DE-42349 Wuppertal-Cronenberg www.knipex.de
Length	130 mm
Width	59 mm
Height	19 mm
Length with packaging	189 mm
Width with packaging	72 mm
Height with packaging	48 mm
Volume with packaging	0.637 dm^3
Sales unit	1 piece
Content unit	1 piece
Type of packaging	single pack
Standards	DIN ISO 9654
RoHS compliant	no
Surface	burnished
VDE	no
Jaw thickness	6.5 mm
ESD compliant	no
Description Head	polished
Grip (expression)	with multi-component sleeves
Length of the jaws	10 mm
Cutting value wire diameter (hard)	0.7 mm
Cutting value wire diameter (medium)	1.3 mm
Cutting value wire diameter (soft)	1.7 mm
Type of pliers	cutting pliers