# Pliers wrench, pliers and wrench in one tool, chrome plated, 180 mm




Pliers wrench replaces a set of spanners, metric as well as imperial. smooth jaws for gentle assembly of surface-finished fittings - work directly on chrome!. Also excellent for gripping, holding, pressing and bending workpieces. No edge damage on sensitive fittings due to backlash-free, full-surface contact. Quick adjustment at the touch of a button directly on the workpiece. No unintentional adjustment of the gripper jaws and no slipping of the joint. Stepless gripping of all spanner sizes up to the specified capacity by means of parallel guided jaws. The stroke between the gripping jaws allows quick tightening and loosening of screw connections according to the ratchet principle. High clamping force due to 10-fold manual force amplification. with narrow gripping jaws - for screwdriving situations requiring a slim tool. - jaw thickness (at joint) (B2): 8.0mm - joint thickness (B3): 12.0mm - tip thickness (B1): 5.0mm - setting positions: 15 - capacity for nuts, width across flats (inches): 1 1/2 - capacity for nuts, width across flats (mm): 40mm

- also excellent for gripping, holding, pressing and bending workpieces

| **Item no.** | **WL61770** |
|---|---|
| Model | 86 03 180 |
| Manufacturer | KNIPEX |
| Manufacturer article no. | 86 03 180 |
| GPSR manufacturer data | KNIPEX-Werk<br>Oberkamper Strasse 13<br>DE-42349 Wuppertal-Cronenberg<br>www.knipex.de |
| Length | 181 mm |
| Width | 44 mm |
| Height | 15 mm |

| | |
|---|---|
| Length with packaging | 191 mm |
| Width with packaging | 60 mm |
| Height with packaging | 21 mm |
| Volume with packaging | 0.241 $dm^3$ |
| Sales unit | 1 piece |
| Content unit | 1 piece |
| Type of packaging | single pack |
| RoHS compliant | no |
| Surface | chrome-plated |
| VDE | no |
| Jaw thickness | 8 mm |
| ESD compliant | no |
| Tool length | 180 mm |
| Description Head | chrome-plated |
| Grip (expression) | covered with plastic |
| Type of pliers | pliers wrench |

## Other versions

| Item no. | Tool length |
|---|---|
| WL61769 | 150 mm |
| **WL61770** | **180 mm** |
| WL13364 | 250 mm |
| WL61771 | 300 mm |
| WL61772 | 400 mm |