

Profile compound pliers, burnished, 340 mm



For making firm connections of profiled sheets used in drywall construction for partition walls and suspended ceilings without the need for screws or rivets. For U and C profiles with max. 1.2 mm sheet thickness (2 x 0.6 mm). Minimal force required due to optimum lever transmission. - Capacity millimetres: max. 1.2 (2 x 0.6)

- For the production of fixed connections of profiled sheets used in dry construction for the erection of partition walls and suspended ceilings without the need for screws or rivets.
- For U and C profiles with max. 1.2 mm sheet thickness (2 x 0.6 mm)
- Minimum effort due to optimum lever transmission

Item no.	WL61850
Model	90 42 340
Manufacturer	KNIPEX
Manufacturer article no.	90 42 340
GPSR manufacturer data	KNIPEX-Werk Oberkamper Strasse 13 DE-42349 Wuppertal-Cronenberg www.knipex.de
Length	340 mm
Width	96 mm
Height	19 mm
Length with packaging	370 mm
Width with packaging	130 mm
Height with packaging	40 mm

Volume with packaging	1.924 dm ³
Sales unit	1 piece
Content unit	1 piece
Type of packaging	single pack
Incl. battery	no
RoHS compliant	no
Surface	burnished
VDE	no
ESD compliant	no
Tool length	340 mm
Grip (expression)	With multi-component sleeves
Type of pliers	special pliers