

Cable shears, handles overmolded with plastic, 165 mm



Not suitable for steel wire and hard-drawn copper conductors. Hardened cutting edges with precision grinding. No crushing, low deformation of the cable. Pinch protection prevents crushing injuries. Adjustable screw joint. For cutting cables $\varnothing 10 \text{ mm} / 24 \text{ mm}^2$. With opening spring and ratchet. Cutting edges made of stainless steel. oil-hardened and tempered. - Cutting value Cu-cable, stranded: 24 mm^2 - Cutting value Cu-cable, stranded: $\varnothing 10 \text{ mm}$ - AWG: 3

- Not suitable for steel wire and hard-drawn copper conductors
- Hardened cutting edges with precision grinding
- No crushing, low deformation of the cable
- Pinch protection prevents crushing injuries
- Adjustable screw joint

item number	WL61889
model	95 05 165
manufacturer	KNIPEX
manufacturer item number	95 05 165
length	165 mm
width	48 mm
height	16 mm
length with packaging	264 mm
width with packaging	94 mm
height with packaging	51 mm
Packaging volume	1.266 dm^3
order unit	1 piece

Products for the electronic industry



content unit	1 piece
type of packaging	single pack
RoHS conform	no
VDE	no
ESD safe	no
tool length	165 mm
AWG	3
description head	polished
type of handle	Overmoulded with plastic
Cutting value copper cable, multistranded	24 mm ²
Cutting value copper cable, multistranded (diameter)	10 mm