

Cable shears with double cutting edge, chrome-plated, insulated, 200 mm



For cutting Cu and Al cables. Not suitable for steel wire and hard-drawn copper conductors. Hardened cutting edges with precision grinding. Cuts smoothly and cleanly without crushing. Adjustable screw joint, self-locking. Low force required due to favourable transmission ratios and special cutting geometry. Pinch protection prevents crushing injuries. Adjustable screw joint, self-locking. - Cutting value Cu-cable, stranded: 70mm² - Cutting value Cu-cable, stranded: Ø 20mm - AWG: 2 / 0 - VDE-tested: Yes

- For cutting Cu and Al cables
- Not suitable for steel wire and hard-drawn copper conductors
- Hardened cutting edges with precision grinding
- Cuts smoothly and cleanly without crushing
- Adjustable screw joint, self-locking
- Low force required due to favourable transmission ratios and special cutting geometry
- Pinch protection prevents crushing injuries
- Adjustable screw joint, self-locking

Item no.	WL61894
Model	95 16 200
Manufacturer	KNIPEX
Manufacturer article no.	95 16 200
GPSR manufacturer data	KNIPEX-Werk Oberkamper Strasse 13 DE-42349 Wuppertal-Cronenberg www.knipex.de

Length	220 mm
Width	68 mm
Height	19 mm
Length with packaging	237 mm
Width with packaging	67 mm
Height with packaging	35 mm
Volume with packaging	0.535 dm ³
Sales unit	1 piece
Content unit	1 piece
Type of packaging	single pack
Incl. battery	no
Standards	DIN EN 60900 IEC 60900
RoHS compliant	no
Surface	chrome-plated
VDE	yes
ESD compliant	no
AWG	2 / 0
Tool length	200 mm
Grip (expression)	VDE insulated with multi-component sheaths, VDE-tested
Cutting value copper cable, stranded	70 mm ²
Cutting value copper cable, stranded (diameter)	20 mm