

## Cable shears for two-hand operation, with plastic sheaths, 600 mm



For cutting copper and aluminium cables, solid and stranded. Not suitable for steel wire and wire ropes. Hardened cutting edges with precision grinding. Cuts smoothly and cleanly without crushing. Favourable transmission ratios due to toggle lever mechanism. Pinch protection prevents crushing injuries. Adjustable screw joint. Bolted cutter head, replaceable. - Cutting value Cu-cable, stranded: 150mm<sup>2</sup> - Cutting value Cu-cable, stranded: Ø 27mm - AWG: 5 / 0

- For cutting Cu- and Al-cables, solid and stranded
- Not suitable for steel wire and wire ropes
- Hardened cutting edges with precision grinding
- Cuts smoothly and cleanly without crushing
- Favourable transmission ratios due to toggle lever mechanism
- Pinch protection prevents crushing injuries
- Adjustable screw joint
- Bolted cutter head, replaceable

item number	WL61898
model	95 21 600
manufacturer	KNIPEX
manufacturer item number	95 21 600
length	580 mm
width	165 mm
height	38 mm
length with packaging	685 mm

Products for the electronic industry



width with packaging	210 mm
height with packaging	65 mm
Packaging volume	9.35 dm <sup>3</sup>
order unit	1 piece
content unit	1 piece
type of packaging	single pack
RoHS conform	no
VDE	no
ESD safe	no
tool length	600 mm
AWG	5 / 0
description head	polished
type of handle	with plastic sheaths
Cutting value copper cable, multistranded	150 mm <sup>2</sup>
Cutting value copper cable, multistranded (diameter)	27 mm