

## Cable shears, burnished, 165 mm



For cutting copper and aluminium cables, solid and stranded. Cuts smoothly and cleanly without crushing. Not suitable for steel wire and hard-drawn copper conductors. Hardened cutting edges with precision grinding. Easy cutting with one-hand operation. With clamping protection. Adjustable screw joint, self-locking. Multi-function tool for processing NYM cables from  $3 \times 1.5 \text{ mm}^2$  to  $5 \times 2.5 \text{ mm}^2$  (cutting and stripping). universal stripping point for both solid conductor cross-sections. secure centring of the cable in the stripping point due to V-shaped cutting geometry. - Shape: 4 - cutting value Cu-cable, stranded:  $35 \text{ mm}^2$  - cutting value Cu-cable, stranded:  $\text{Ø } 12 \text{ mm}$  - AWG: 1 / 0

- For cutting Cu and Al cables, solid and stranded
- Cuts smoothly and cleanly without crushing
- Not suitable for steel wire and hard drawn copper conductors
- Hardened cutting edges with precision grinding
- Easy cutting with one hand operation
- With clamping protection
- Adjustable screw joint, self-locking

item number	WL61925
model	95 41 165
manufacturer	KNIPEX
manufacturer item number	95 41 165
length	165 mm
width	42 mm
height	15 mm
length with packaging	213 mm
width with packaging	75 mm

Products for the electronic industry



height with packaging	49 mm
Packaging volume	0.783 dm <sup>3</sup>
order unit	1 piece
content unit	1 piece
type of packaging	single pack
RoHS conform	no
surface	burnished
VDE	no
ESD safe	no
tool length	165 mm
AWG	1 / 0
type of handle	Covered with plastic
Cutting value copper cable, multistranded	35 mm <sup>2</sup>
Cutting value copper cable, multistranded (diameter)	12 mm