

Wire rope cutter, forged, 190 mm



With two press profiles for end sleeves on Bowden sheaths and end caps for wire rope hoists. Comfortable working due to handy, slim design and internal opening spring. Bolted joint for precise blade guidance, adjustable. High transmission ratio for effort-saving work. Cutting edge hardness approx. 64 HRC. - Cutting value Cu-cable, stranded: 10mm² - Cutting value Cu-cable, stranded (diameter): Ø 7,0mm - Cutting value Cu-cable, fine stranded (diameter): Ø 6,0mm² - Cutting value wire (diameter): Ø 5,0mm - Cutting value medium hard wire (diameter): Ø 4,0mm - Cutting value piano wire (diameter): Ø 2,5mm - Cutting value iron (diameter): Ø 4mm - AWG: 7

- With two press profiles for end sleeves on Bowden sheaths and end caps for wire ropes
- Comfortable working due to handy, slim design and internal opening spring
- Bolted joint for precise blade guidance, adjustable
- High transmission ratio for effort-saving work
- Cutting edge hardness approx. 64 HRC

Item no.	WL61927
Model	95 61 190
Manufacturer	KNIPEX
Manufacturer article no.	95 61 190
GPSR manufacturer data	KNIPEX-Werk Oberkamper Strasse 13 DE-42349 Wuppertal-Cronenberg www.knipex.de
Length	195 mm
Width	60 mm
Height	20 mm
Length with packaging	229 mm
Width with packaging	119 mm

Products for the electronic industry



Height with packaging	52 mm
Volume with packaging	1.417 dm ³
Sales unit	1 piece
Content unit	1 piece
Type of packaging	single pack
Incl. battery	no
RoHS compliant	no
VDE	no
ESD compliant	no
AWG	7
Tool length	190 mm
Description Head	polished
Grip (expression)	covered with plastic
Cutting value copper cable, stranded	10 mm ²
Cutting value copper cable, stranded (diameter)	7 mm
Cutting value wire diameter (medium)	4 mm