

Wire rope and cable shears, dip-insulated, 600 mm



For wire ropes and round bars, Cu and Al cables. Suitable for cutting overhead cables with strain relief wire. Angled cutting tips enable cutting of individual rope strands. Optimum transmission ratio for high cutting performance. Bolted cutter head, replaceable. Low weight. - Cutting value Cu-cable, stranded: 150mm² - Cutting value Cu-cable, fine stranded (diameter): Ø 14,0mm² - Cutting value wire rope (diameter): Ø 14,0mm - Cutting value medium hard wire (diameter): Ø 9,0mm - Cutting value iron (diameter): Ø 9mm - AWG: 5 / 0

- For wire ropes and round bars, Cu and Al cables
- Suitable for cutting overhead cables with strain relief wire
- Angled cutting tips enable cutting of individual rope strands
- Optimum transmission ratio for high cutting performance
- Bolted cutter head, replaceable
- Low weight

item number	WL61933
model	95 77 600
manufacturer	KNIPEX
manufacturer item number	95 77 600
length	615 mm
width	230 mm
height	37 mm
length with packaging	610 mm
width with packaging	215 mm
height with packaging	35 mm
Packaging volume	4.59 dm ³

order unit	1 piece
content unit	1 piece
type of packaging	single pack
standards	DIN EN 60900 IEC 60900
RoHS conform	no
VDE	no
ESD safe	no
tool length	600 mm
AWG	5 / 0
description head	polished
type of handle	Immersion-insulated
Cutting value copper cable, multistranded	150 mm ²
cutting value wire diameter medium	9 mm

