

Self-adjusting crimping pliers for ferrules with side entry, burnished, 180 mm, sales packaging



Self-adjusting crimping pliers for wire end ferrules with smaller grip width. For crimping wire-end ferrules according to DIN 46228 Part 1 + 4. Self-adjusting adjustment to the required ferrule size. Consistently high crimp quality due to positive lock (can be unlocked). Crimp pressure is precisely set (calibrated) at the factory. Force amplification through toggle lever for fatigue-free operation. High operating comfort due to handy design and low weight. Hexagonal crimping with capacity extension up to 10 mm². Hexagonal crimping for confined connection dimensions. especially suitable for all twin wire-end ferrules up to 2 x 4 mm² or 2 x AWG 10. - Application: Wire end ferrules - Capacity square millimetres: 0.08 - 16mm², per switch handle and all twin ferrules up to 2 x 10 mm² (AWG 2 x 8) - Number of nests: 1 - AWG: 28 - 7.

- For crimping ferrules according to DIN 46228 part 1 + 4
- Self-adjusting adjustment to the desired ferrule size
- Consistently high crimp quality due to positive lock (can be unlocked)
- Crimp pressure is precisely set (calibrated) at the factory
- Force amplification through toggle lever for low-fatigue work
- High ease of use due to handy design and low weight
- can also crimp twin wire-end ferrules

item number

WL62026

Products for the electronic industry



model	97 53 14 SB
manufacturer	KNIPEX
manufacturer item number	97 53 14 SB
length	176 mm
width	74 mm
height	25 mm
length with packaging	271 mm
width with packaging	115 mm
height with packaging	33 mm
Packaging volume	1.028 dm ³
order unit	1 piece
content unit	1 piece
type of packaging	blister packaging
RoHS conform	no
surface	burnished
VDE	no
application crimp	Wire end ferrules
Number of crimp nests	1
crimp profile	Hexagonal crimp automatic
ESD safe	no
tool length	180 mm
AWG	28 - 7
type of handle	with multi-component sleeves
type of pliers	automatic crimping tool