Self-adjusting crimping pliers for ferrules with side entry, 0.08 - 10/16 mm², chrome-plated, 180 mm, sales packaging



Self-adjusting crimping pliers for wire end ferrules with smaller grip width. For crimping wire-end ferrules according to DIN 46228 Parts 1 + 4. Self-adjusting adjustment to the required ferrule size. Consistently high crimp quality due to positive lock (can be unlocked). Crimp pressure is precisely set (calibrated) at the factory. Force amplification through toggle lever for fatigue-free operation. High operating comfort due to handy design and low weight. Square crimping also for wire end ferrules up to 16 mm². Square crimping for optimum contact surfaces in the terminal connection. - Application: Wire end ferrules - Capacity square millimetres: 0.08 - 10 / 16mm² - Number of nests: 1 - AWG: 28 - 5.

- For crimping ferrules according to DIN 46228 part 1 + 4
- Self-adjusting adjustment to the desired ferrule size
- Consistently high crimp quality due to positive lock (can be unlocked)
- Crimping pressure is precisely set (calibrated) at the factory
- Force amplification through toggle lever for fatigue-free operation
- High operating comfort due to handy design and low weight

Item no.	**WL62029**
Model	97 55 04 SB
Manufacturer	KNIPEX
Manufacturer article no.	97 55 04 SB
GPSR manufacturer data	KNIPEX-Werk Oberkamper Strasse 13

	DE-42349 Wuppertal-Cronenberg www.knipex.de
Length	270 mm
Width	114 mm
Height	32 mm
Length with packaging	270 mm
Width with packaging	114 mm
Height with packaging	32 mm
Volume with packaging	1.095 dm^3
Sales unit	1 piece
Content unit	1 piece
Type of packaging	blister packaging
RoHS compliant	no
Surface	chrome-plated
VDE	no
Crimping application	Wire end ferrules
Number of crimp nests	1
ESD compliant	no
AWG	28 - 5
Crimp profile	Square crimp
Tool length	180 mm
Description Head	chrome-plated
Grip (expression)	with multi-component sleeves
Type of pliers	automatic crimping tool