

Self-adjusting crimping pliers for end sleeves (ferrules) with side entry, 0.08 - 10 mm², chrome-plated, 180 mm



Self-adjusting crimping pliers for wire end ferrules with smaller grip width. For crimping wire-end ferrules according to DIN 46228 Parts 1 + 4. Self-adjusting adjustment to the required ferrule size. Consistently high crimp quality due to positive lock (can be unlocked). Crimp pressure is precisely set (calibrated) at the factory. Force amplification through toggle lever for fatigue-free operation. High operating comfort due to handy design and low weight. Hexagonal crimping with capacity extension up to 10 mm². Hexagonal crimping for confined connection dimensions. especially suitable for all twin wire-end ferrules up to 2 x 4 mm² or 2 x AWG 10. - Application: Wire end ferrules - Capacity square millimetres: 0.08 - 10mm² - Number of nests: 1 - AWG: 28 - 7.

- For crimping wire end ferrules according to DIN 46228 part 1 + 4
- Self-adjusting adjustment to the desired ferrule size
- Consistently high crimp quality due to positive lock (can be unlocked)
- Crimping pressure is precisely set (calibrated) at the factory
- Force amplification through toggle lever for fatigue-free operation
- High operating comfort due to handy design and low weight

item number	WL62032
model	97 55 14
manufacturer	KNIPEX
manufacturer item number	97 55 14

length	180 mm
width	75 mm
height	21 mm
length with packaging	180 mm
width with packaging	75 mm
height with packaging	21 mm
Packaging volume	0.284 dm ³
order unit	1 piece
content unit	1 piece
type of packaging	single pack
RoHS conform	no
surface	chrome-plated
VDE	no
application crimp	Wire end ferrules
Number of crimp nests	1
crimp profile	Hexagonal crimp automatic
ESD safe	no
tool length	180 mm
AWG	28 - 7
description head	chrome-plated
type of handle	with multi-component sleeves
type of pliers	automatic crimping tool