

Crimping pliers for ferrules, 0.25 - 2.5 mm², 145 mm, sales packaging



for wire end ferrules: For crimping wire end ferrules DIN 46228 part 1 + 4 in the range of 0.25 to 2.5 mm². Crimping in marked trapezoidal profiles for secure connection of sleeve and conductor. - Application: Wire end ferrules - Capacity square millimetres: 0.25 - 2.5mm² - Number of nests: 4 - AWG: 23 - 13.

- For crimping wire end ferrules DIN 46228 part 1 + 4 in the range of 0.25 to 2.5 mm².
- Crimping in marked trapezoidal profiles for secure connection of sleeve and conductor

Item no.	WL62037
Model	97 61 145 A SB
Manufacturer	KNIPEX
Manufacturer article no.	97 61 145 A SB
GPSR manufacturer data	KNIPEX-Werk Oberkamper Strasse 13 DE-42349 Wuppertal-Cronenberg www.knipex.de
Length	145 mm
Width	84 mm
Height	13 mm
Length with packaging	253 mm
Width with packaging	115 mm
Height with packaging	92 mm
Volume with packaging	2.677 dm ³

Products for the electronic industry



Sales unit	1 piece
Content unit	1 piece
Type of packaging	blister packaging
Incl. battery	no
RoHS compliant	no
VDE	no
Crimping application	Wire end ferrules
Number of crimp nests	4
ESD compliant	no
AWG	23 - 13
Crimp profile	Trapezoidal crimp
Tool length	145 mm
Description Head	polished
Grip (expression)	covered with plastic
Type of pliers	crimping pliers