

Wire end ferrules, uninsulated, 2.5 mm², pure tin-plated, 200 pieces



With wire end ferrules, uninsulated, cable 2.5 mm², pure tin-plated, 200 pieces, Knipex offers a high-quality connecting element that has been specially developed for professional applications in control and distribution systems. The material behavior under pressure and temperature is ideally suited to industrial requirements in demanding environments. These wire end ferrules are therefore an ideal choice for use in control cabinet construction, machine installation or industrial maintenance.

Item no.	WL62143
Model	97 99 394
Manufacturer	KNIPEX
Manufacturer article no.	97 99 394

Products for the electronic industry



GPSR manufacturer data

KNIPEX-Werk
 Oberkamper Strasse 13
 DE-42349 Wuppertal-Cronenberg
 www.knipex.de

Length	120 mm
Width	135 mm
Height	15 mm
Length with packaging	120 mm
Width with packaging	135 mm
Height with packaging	15 mm
Volume with packaging	0.135 dm ³
Sales unit	1 PU
Content unit	200 piece
Standards	DIN 46228-1
RoHS compliant	no
VDE	no
ESD compliant	no
Cable cross-section	2.5 mm ²
AWG	13

Other versions

Item no.	Cable cross-section
WL62139	0.5 mm ²
WL62140	0.75 mm ²
WL62141	1 mm ²
WL62142	1.5 mm ²
WL62143	2.5 mm²
WL62144	4 mm ²