

Socket wrench with screwdriver handle, burnished, insulated, key width 12 mm, 237 mm



Ergonomically optimised 2-component handle for low-fatigue and hand-friendly power transmission. Anti-roll handle shape. - Width across flats S: 12.0mm - Handle length max.: 112mm - Head diameter d: 20mm Blade length 125mm - VDE-tested: Yes

- Ergonomically optimised 2-component handle for low-fatigue and hand-friendly power transmission
- Anti-roll handle shape

item number	WL62205
model	98 03 12
manufacturer	KNIPEX
manufacturer item number	98 03 12
GPSR manufacturer information	KNIPEX-Werk Oberkamper Strasse 13 DE-42349 Wuppertal-Cronenberg www.knipex.de
length	235 mm
width	35 mm
height	32 mm
length with packaging	325 mm
width with packaging	124 mm
height with packaging	86 mm
Packaging volume	3.466 dm ³
order unit	1 piece
content unit	1 piece

Products for the electronic industry



type of packaging	single pack
standards	DIN EN 60900 IEC 60900
RoHS conform	no
surface	burnished
VDE	yes
ESD safe	no
tool length	237 mm
type of handle	VDE insulating multi-component handle, VDE-tested
blade length	125 mm
wrench width	12 mm

Other versions

item number	tool length	wrench width
WL62196	230 mm	4 mm
WL62197	230 mm	5 mm
WL62198	232 mm	5.5 mm
WL62199	232 mm	6 mm
WL62200	237 mm	7 mm
WL62201	237 mm	8 mm
WL62202	237 mm	9 mm
WL62203	237 mm	10 mm
WL62204	237 mm	11 mm
WL62205	237 mm	12 mm
WL62206	237 mm	13 mm