

## Roller fork wrench, chrome-plated, dip-insulated, 260 mm



Parallel guided, smooth gripping jaws. Width across flats infinitely variable. With scale for setting the wrench width away from the workpiece. - Jaw width: 8mm - Head width (W3): 16mm - Depth: 20mm - Width: 2in - Capacity for nuts, width across flats (mm): 30mm - Capacity for nuts, width across flats (inches): 1 1/8in

- Parallel guided, smooth jaws
- Width across flats infinitely adjustable
- With scale for setting the wrench width away from the workpiece

<b>Item no.</b>	<b>WL62216</b>
Model	98 07 250
Manufacturer	KNIPEX
Manufacturer article no.	98 07 250
GPSR manufacturer data	KNIPEX-Werk Oberkamper Strasse 13 DE-42349 Wuppertal-Cronenberg www.knipex.de
Length	267 mm
Width	78 mm
Height	32 mm
Depth	20 mm
Length with packaging	270 mm
Width with packaging	81 mm
Height with packaging	40 mm
Volume with packaging	0.899 dm <sup>3</sup>

Sales unit	1 piece
Content unit	1 piece
Type of packaging	single pack
Standards	DIN EN 60900   IEC 60900
RoHS compliant	no
Surface	chrome-plated
VDE	no
Jaw angle	Jaws, angled, 22
ESD compliant	no
Tool length	260 mm
Grip (expression)	Dip-insulated