

Screwdriver (slim), for slotted screws, black oxide finish, insulated, 202 mm



Screwdriver (Slim) for slotted screws: Reduced blade insulation diameter for low-lying spring and screw elements.: Ergonomically optimised 2-component handle for low-fatigue and hand-friendly power transmission. Anti-roll handle shape. - Blade length: 100mm - uninsulated blade length: 15mm - handle length: 102mm - cutting edge width: 3.5mm - cutting edge thickness: 0.6mm - VDE-tested: Yes

- Reduced blade insulation diameter for low-lying spring and screw elements
- Ergonomically optimised 2-component handle for low-fatigue and hand-friendly power transmission
- Anti-roll handle shape

Item no.	WL62232
Model	98 20 35 SL
Manufacturer	KNIPEX
Manufacturer article no.	98 20 35 SL
GPSR manufacturer data	KNIPEX-Werk Oberkamper Strasse 13 DE-42349 Wuppertal-Cronenberg www.knipex.de
Length	200 mm
Width	25 mm
Height	23 mm
Length with packaging	236 mm
Width with packaging	88 mm
Height with packaging	52 mm
Volume with packaging	1.104 dm ³
Sales unit	1 piece

Products for the electronic industry



Content unit	1 piece
Type of packaging	single pack
Incl. battery	no
Standards	DIN EN 60900 IEC 60900
RoHS compliant	no
Surface	burnished
VDE	yes
Screw type	slot
ESD compliant	no
Screwdriver type	normal screwdrivers
Cutting thickness	0.6 mm
Tool length	202 mm
Grip (expression)	VDE insulating multi-component handle, VDE-tested
Blade length	100 mm
Cutting width	3.5 mm

Other versions

Item no.	Cutting thickness & Cutting width	Blade length
WL62232	0.6 mm & 3.5 mm	100 mm
WL62234	0.8 mm & 4 mm	100 mm
WL62236	1 mm & 5.5 mm	125 mm
WL62238	1.2 mm & 6.5 mm	150 mm