

Screwdriver for slotted screws, black oxide finish, insulated, 202 mm



Screwdriver for slotted screws: Ergonomically optimised 2-component handle for low-fatigue and hand-friendly power transmission. Anti-roll handle shape. - Blade length: 100mm - Uninsulated blade length: 15mm - Handle length: 102mm - Blade width: 4.0mm - Blade thickness: 0.8mm - VDE-tested: Yes

- Ergonomically optimised 2-component handle for low-fatigue and hand-friendly power transmission
- Anti-roll handle shape

| | |
|--------------------------|--|
| Item no. | WL62235 |
| Model | 98 20 40 |
| Manufacturer | KNIPEX |
| Manufacturer article no. | 98 20 40 |
| GPSR manufacturer data | KNIPEX-Werk Oberkamper Strasse 13 DE-42349 Wuppertal-Cronenberg www.knipex.de |
| Length | 200 mm |
| Width | 25 mm |
| Height | 24 mm |
| Length with packaging | 236 mm |
| Width with packaging | 88 mm |
| Height with packaging | 52 mm |
| Volume with packaging | 1.104 dm ³ |
| Sales unit | 1 piece |
| Content unit | 1 piece |

Products for the electronic industry



| | |
|-------------------|---|
| Type of packaging | single pack |
| Standards | DIN EN 60900 IEC 60900 |
| RoHS compliant | no |
| Surface | burnished |
| VDE | yes |
| Screw type | slot |
| ESD compliant | no |
| Screwdriver type | normal screwdrivers |
| Cutting thickness | 0.8 mm |
| Tool length | 202 mm |
| Grip (expression) | VDE insulating multi-component handle, VDE-tested |
| Blade length | 100 mm |
| Cutting width | 4 mm |

Other versions

| Item no. | Cutting thickness | Cutting width | Blade length |
|----------------|-------------------|---------------|---------------|
| WL62230 | 0.4 mm | 2.5 mm | 75 mm |
| WL62231 | 0.5 mm | 3 mm | 100 mm |
| WL62233 | 0.6 mm | 3.5 mm | 100 mm |
| WL62235 | 0.8 mm | 4 mm | 100 mm |
| WL62237 | 1 mm | 5.5 mm | 125 mm |
| WL62239 | 1.2 mm | 6.5 mm | 150 mm |
| WL62240 | 1.2 mm | 8 mm | 175 mm |
| WL62229 | 1.6 mm | 10 mm | 200 mm |