Screwdriver (slim), for Phillips® cross-head screws, black oxide finish, insulated, 212 mm



Screwdriver (Slim) for cross-slotted head screws: Reduced blade insulation diameter for low-lying spring and screw elements..: Ergonomically optimised 2-component handle for low-fatigue and hand-friendly power transmission. Anti-roll handle shape. - Size: PH2 - Blade length: 100mm - Handle length: 112mm - Uninsulated blade length: 18mm - VDE-tested: Yes

- Reduced blade insulation diameter for low-lying spring and screw elements
- Ergonomically optimised 2-component handle for low-fatigue and hand-friendly power transmission
- Anti-roll handle shape

Item no.	**WL62246**
Model	98 24 02 SL
Manufacturer	KNIPEX
Manufacturer article no.	98 24 02 SL
GPSR manufacturer data	KNIPEX-Werk Oberkamper Strasse 13 DE-42349 Wuppertal-Cronenberg www.knipex.de
Length	210 mm
Width	33 mm
Height	35 mm
Length with packaging	324 mm
Width with packaging	124 mm
Height with packaging	51 mm

Volume with packaging	2.066 dm^3
Sales unit	1 piece
Content unit	1 piece
Type of packaging	single pack
Standards	DIN EN 60900 | IEC 60900
RoHS compliant	no
Surface	burnished
VDE	yes
Screw type	mixed
ESD compliant	no
Screwdriver type	1000 V insulated
Tool length	212 mm
Grip (expression)	VDE | insulating multi-component handle, VDE-tested
Blade length	100 mm

Other versions

Item no.	Tool length & Blade length
WL62243	187 mm & 80 mm
WL62246	**212 mm & 100 mm**