

Screwdriver for Phillips® cross-head screws, black oxide finish, insulated, 320 mm



Screwdriver for cross-slotted head screws: Ergonomically optimised 2-component handle for low-fatigue and hand-friendly power transmission. Anti-roll handle shape. - Size: PH4 - Blade length: 200mm - Handle length: 120mm - Blade Ø: 10.0mm - Uninsulated blade length: 18mm - VDE-tested: Yes

- Ergonomically optimised 2-component handle for low-fatigue and hand-friendly power transmission
- Anti-roll handle shape

Item no.	WL62250
Model	98 24 04
Manufacturer	KNIPEX
Manufacturer article no.	98 24 04
GPSR manufacturer data	KNIPEX-Werk Oberkamper Strasse 13 DE-42349 Wuppertal-Cronenberg www.knipex.de
Length	315 mm
Width	37 mm
Height	36 mm
Length with packaging	325 mm
Width with packaging	123 mm
Height with packaging	86 mm
Volume with packaging	3.456 dm ³
Sales unit	1 piece
Content unit	1 piece

Products for the electronic industry



Type of packaging	single pack
Incl. battery	no
Standards	DIN EN 60900 IEC 60900
RoHS compliant	no
Surface	burnished
VDE	yes
Screw type	mixed
ESD compliant	no
Screwdriver type	1000 V insulated
Tool length	320 mm
Grip (expression)	VDE insulating multi-component handle, VDE-tested
Blade diameter	10 mm
Blade length	200 mm

Other versions

Item no.	Tool length & Blade length
WL62242	162 mm & 60 mm
WL62245	187 mm & 80 mm
WL62248	212 mm & 100 mm
WL62249	270 mm & 150 mm
WL62250	320 mm & 200 mm