

Screwdriver for Pozidriv® cross-head screws, black oxide finish, insulated, 162 mm



Screwdrivers for cross-slotted head screws: Ergonomically optimised 2-component handle for low-fatigue and hand-friendly power transmission. Anti-roll handle shape. - Size: PZO - Blade length: 60mm - Handle length: 102mm - Blade Ø: 3.0mm - Uninsulated blade length: 15mm - VDE-tested: Yes

- Ergonomically optimised 2-component handle for low-fatigue and hand-friendly power transmission
- Anti-roll handle shape

Item no.	WL62251
Model	98 25 00
Manufacturer	KNIPEX
Manufacturer article no.	98 25 00
GPSR manufacturer data	KNIPEX-Werk Oberkamper Strasse 13 DE-42349 Wuppertal-Cronenberg www.knipex.de
Length	160 mm
Width	25 mm
Height	25 mm
Length with packaging	236 mm
Width with packaging	88 mm
Height with packaging	52 mm
Volume with packaging	1.104 dm ³
Sales unit	1 piece

Products for the electronic industry



Content unit	1 piece
Type of packaging	single pack
Incl. battery	no
Standards	DIN EN 60900 IEC 60900
RoHS compliant	no
Surface	burnished
VDE	yes
Screw type	mixed
ESD compliant	no
Screwdriver type	1000 V insulated
Tool length	162 mm
Grip (expression)	VDE insulating multi-component handle, VDE-tested
Blade diameter	3 mm
Blade length	60 mm

Other versions

Item no.	Tool length & Blade length
WL62251	162 mm & 60 mm
WL62254	187 mm & 80 mm
WL62257	212 mm & 100 mm
WL62258	270 mm & 150 mm
WL62259	320 mm & 200 mm