

Screwdriver (slim), for Pozidriv® cross-head screws, black oxide finish, insulated, 187 mm



Screwdriver (Slim) for cross-slotted head screws: Reduced blade insulation diameter for low-lying spring and screw elements.: Ergonomically optimised 2-component handle for low-fatigue and hand-friendly power transmission. Anti-roll handle shape. - Size: PZ1 - Blade length: 80mm - Handle length: 107mm - Uninsulated blade length: 15mm - VDE-tested: Yes

- Reduced blade insulation diameter for low-lying spring and screw elements
- Ergonomically optimised 2-component handle for low-fatigue and hand-friendly power transmission
- Anti-roll handle shape

Item no.	WL62252
Model	98 25 01 SL
Manufacturer	KNIPEX
Manufacturer article no.	98 25 01 SL
GPSR manufacturer data	KNIPEX-Werk Oberkamper Strasse 13 DE-42349 Wuppertal-Cronenberg www.knipex.de
Length	185 mm
Width	28 mm
Height	30 mm
Length with packaging	236 mm
Width with packaging	88 mm
Height with packaging	52 mm

Products for the electronic industry



Volume with packaging	1.104 dm ³
Sales unit	1 piece
Content unit	1 piece
Type of packaging	single pack
Incl. battery	no
Standards	DIN EN 60900 IEC 60900
RoHS compliant	no
Surface	burnished
VDE	yes
Screw type	mixed
ESD compliant	no
Screwdriver type	1000 V insulated
Tool length	187 mm
Grip (expression)	VDE insulating multi-component handle, VDE-tested
Blade length	80 mm

Other versions

Item no.	Tool length & Blade length
WL62252	187 mm & 80 mm
WL62255	212 mm & 100 mm