

Screwdriver for Torx® screws TX25, black oxide finish, insulated, 185 mm



Screwdriver for Torx® screws: Ergonomically optimised 2-component handle for low-fatigue and hand-friendly power transmission. Anti-roll handle shape. - Size: TX25 - Blade length: 80mm - Handle length: 107mm - Uninsulated blade length: 15mm - VDE-tested: Yes

- Ergonomically optimised 2-component handle for low-fatigue and hand-friendly power transmission
- Anti-roll handle shape

Item no.	WL62263
Model	98 26 25
Manufacturer	KNIPEX
Manufacturer article no.	98 26 25
GPSR manufacturer data	KNIPEX-Werk Oberkamper Strasse 13 DE-42349 Wuppertal-Cronenberg www.knipex.de
Length	315 mm
Width	37 mm
Height	36 mm
Length with packaging	324 mm
Width with packaging	124 mm
Height with packaging	51 mm
Volume with packaging	2.066 dm ³
Sales unit	1 piece

Products for the electronic industry



Content unit	1 piece
Type of packaging	single pack
Incl. battery	no
Standards	DIN EN 60900 IEC 60900
RoHS compliant	no
Surface	burnished
VDE	yes
Screw type	TX25
ESD compliant	no
Screwdriver type	1000 V insulated
Tool length	185 mm
Grip (expression)	VDE insulating multi-component handle, VDE-tested
Blade length	80 mm

Other versions

Item no.	Screw type
WL62260	TX10
WL62261	TX15
WL62262	TX20
WL62263	TX25
WL62264	TX30