

Tool roll-up bag, 15-piece, with insulated tools for working on electrical systems



Roll-up bag made of hard-wearing polyester fabric. With practical, adjustable quick-release fastener. Equipped with an assortment of insulated KNIPEX tools for working on electrical installations. Dimensions, opened (L x H): 830 x 310 mm. Scope of delivery: 1 x 11 07 160 KNIPEX stripping pliers with opening spring, universal ($\varnothing$ 5.0 mm / 10.0 mm²), 1 x 98 52 KNIPEX cable knife, 1 x 95 17 200 KNIPEX cable shears with double cutting edge ($\varnothing$ 20 mm / 70 mm²), 1 x 03 07 200 KNIPEX combination pliers (For flat and round material), 1 x 98 20 25 KNIPEX screwdriver for slotted screws (2.5 mm), 1 x 98 20 40 KNIPEX screwdriver for slotted screws (4.0 mm), 1 x 98 20 55 KNIPEX screwdriver for slotted screws (5.5 mm), 1 x 98 20 65 KNIPEX screwdriver for slotted screws (6.5 mm), 1 x 98 00 10 KNIPEX open-end wrench (10 mm), 1 x 98 00 13 KNIPEX open-end wrench (13 mm), 1 x 98 00 14 KNIPEX open-end wrench (14 mm), 1 x 98 00 17 KNIPEX open-ended spanner (17 mm), 1 x 98 00 19 KNIPEX open-ended spanner (19 mm), 1 x 70 07 160 KNIPEX side cutters, 1 x 26 17 200 KNIPEX flat round nose pliers with cutting edge (Stork's nose pliers) (For narrow working areas),

- Roll-up case made of hard-wearing polyester fabric
- With practical, adjustable quick release fastener
- Equipped with an assortment of insulated KNIPEX tools for working on electrical installations
- Dimensions, opened (L x H): 830 x 310 mm

Item no.	WL62354
Model	98 99 13
Manufacturer	KNIPEX
Manufacturer article no.	98 99 13
GPSR manufacturer data	KNIPEX-Werk Oberkamper Strasse 13 DE-42349 Wuppertal-Cronenberg www.knipex.de
Length	310 mm
Width	173 mm
Height	130 mm
Length with packaging	340 mm
Width with packaging	108 mm
Height with packaging	176 mm
Volume with packaging	6.463 dm ³
Scope of delivery	1x 03 07 200 1x 11 07 160 1x 26 17 200 1x 70 07 160 1x 95 17 200 1x 98 00 10 1x 98 00 13 1x 98 00 14 1x 98 00 17 1x 98 00 19 1x 98 20 25 1x 98 20 40 1x 98 20 55 1x 98 20 65 1x 98 52
Sales unit	1 piece
Content unit	1 piece
Incl. battery	no
Standards	DIN EN 60900 IEC 60900
RoHS compliant	no
VDE	no
ESD compliant	no