

Microscope stand MSL3-66 PW, with transmitted and ring light, clamping diameter up to 66 mm



- Microscope stand MSL3-66 PW
- with transmitted and ring light
- Clamping diameter up to 66 mm
- Color rendering index transmitted light: ≥ 80
- Diameter of light surface: approx. 70 mm
- brightness control 0 - 100% with memory function
- Height ring light: 25,5 mm
- Outer diameter ring light: 99 mm
- Inner diameter ring light: 66 mm
- Internal thread ring light: M67 $\times$ 0.75
- Diameter stand column: 32 mm h9
- Height of stand column: 370 mm
- Dimensions of stand plate (L $\times$ W $\times$ H): 300 mm $\times$ 230 mm $\times$ 35 mm

- Distance between stand column and working area: 150 mm - 161 mm

Item no.	WL62538
Manufacturer	STARLIGHT
Manufacturer article no.	100-011603
GPSR manufacturer data	STARLIGHT Opto-Electronics Flachslander Straße 8 DE-90431 Nürnberg www.starlight-sl.de
Sales unit	1 piece
Content unit	1 piece
Manufacturer colour information	black
Colour	black
Material	anodized aluminium / stainless steel
Incl. battery	no
Light source	LED
(Optimal) working distance	80 mm
Luminous flux	200 lm
Number of LEDs	48
Working distance	50 mm - 150 mm
Colour temperature	5700 °K
Power consumption	12 W
ESD compliant	no