

## Microscope stand MSL3-66 NW, with transmitted and ring light, clamping diameter up to 66 mm

---



- Microscope stand MSL3-66 NW
- with transmitted and ring light
- Clamping diameter up to 66 mm
- Colour rendering index transmitted light:  $\geq 80$
- Diameter of light surface: approx. 70 mm
- brightness control 0 - 100% with memory function
- Height ring light: 25,5 mm
- Outer diameter ring light: 99 mm
- Inner diameter ring light: 66 mm
- Internal thread ring light: M67  $\times$  0.75
- Diameter stand column: 32 mm h9
- Height of stand column: 370 mm
- Dimensions of stand plate (L  $\times$  W  $\times$  H): 300 mm  $\times$  230 mm  $\times$  35 mm

- Distance between stand column and working area: 150 mm - 161 mm

|                                 |                                                                                                 |
|---------------------------------|-------------------------------------------------------------------------------------------------|
| <b>Item no.</b>                 | <b>WL62577</b>                                                                                  |
| Manufacturer                    | STARLIGHT                                                                                       |
| Manufacturer article no.        | 100-011758                                                                                      |
| GPSR manufacturer data          | STARLIGHT Opto-Electronics<br>Flachslander Straße 8<br>DE-90431 Nürnberg<br>www.starlight-sl.de |
| Sales unit                      | 1 piece                                                                                         |
| Content unit                    | 1 piece                                                                                         |
| Manufacturer colour information | black                                                                                           |
| Colour                          | black                                                                                           |
| Material                        | anodized aluminium / stainless steel                                                            |
| Incl. battery                   | no                                                                                              |
| Light source                    | LED                                                                                             |
| (Optimal) working distance      | 80 mm                                                                                           |
| Luminous flux                   | 200 lm                                                                                          |
| Number of LEDs                  | 48                                                                                              |
| Working distance                | 50 mm - 150 mm                                                                                  |
| Colour temperature              | 5700 °K                                                                                         |
| Power consumption               | 12 W                                                                                            |
| ESD compliant                   | no                                                                                              |