

LED ring light UV and IR, UV (405 nm), clamping diameter max. 66 mm



- Ringlight UV and IR RL4-66 UV405
- UV (405 nm)
- Clamping diameter max. 66 mm

| | |
|--------------------------|-------------------------------------------------------------------------------------------------|
| Item no. | WL62677 |
| Manufacturer | STARLIGHT |
| Manufacturer article no. | 100-010132 |
| GPSR manufacturer data | STARLIGHT Opto-Electronics Flachslander Straße 8 DE-90431 Nürnberg www.starlight-sl.de |
| Height | 25.5 mm |

Products for the electronic industry



| | |
|---------------------------------|--------------------|
| Sales unit | 1 piece |
| Content unit | 1 piece |
| Manufacturer colour information | black |
| Colour | black |
| Material | anodized aluminium |
| Incl. battery | no |
| Light source | LED |
| Inner diameter | 66 mm |
| Outer diameter | 99 mm |
| (Optimal) working distance | 80 mm |
| Number of LEDs | 48 |
| Working distance | 50mm - 150mm |
| Internal thread | M67 x 0,75 |
| Power cable length | 0.85 m |
| Colour of light | IR, UV |
| Cable length | 1.4 m |
| Power consumption | 7 W |
| ESD compliant | no |