

**LED ring light UV and IR, UV (385 nm), working distance 120 mm, clamping diameter max. 40 mm**

---



- Ringlight UV and IR RL40-120 UV385
- UV (385 nm)
- working distance 120 mm
- Clamping diameter max. 40 mm

|                          |                                                                                                                                          |
|--------------------------|------------------------------------------------------------------------------------------------------------------------------------------|
| Item no.                 | WL62684                                                                                                                                  |
| Manufacturer             | STARLIGHT                                                                                                                                |
| Manufacturer article no. | 100-012293                                                                                                                               |
| GPSR manufacturer data   | STARLIGHT Opto-Electronics<br>Flachslander Straße 8<br>DE-90431 Nürnberg<br><a href="http://www.starlight-sl.de">www.starlight-sl.de</a> |

---

Products for the electronic industry



|                                 |                    |
|---------------------------------|--------------------|
| Height                          | 25.1 mm            |
| Sales unit                      | 1 piece            |
| Content unit                    | 1 piece            |
| Manufacturer colour information | black              |
| Colour                          | black              |
| Material                        | anodized aluminium |
| Inner diameter                  | 30 mm              |
| Outer diameter                  | 58 mm              |
| Number of LEDs                  | 8                  |
| Internal thread                 | M30,5 x 0,5        |
| Power cable length              | 0.85 m             |
| Colour of light                 | IR, UV             |
| Cable length                    | 1.4 m              |
| Power consumption               | 6 W                |
| ESD compliant                   | no                 |

