

Spare jaws felt/velcro 50mm (pair)



The 50 mm protective jaws consist of a felt covering with pressure lock and are designed to be attached to our ball joint vise 9-205-K.

The high-quality felt covering protects sensitive parts from scratches or damage. The pressure lock is a type of Velcro tape with very stable and precise fixation. By simply pressing together - whereby small mushroom heads interlock - a very firm but removable connection is created. The pressure fastener can be crossed, staggered or overlapped. It provides a permanent mechanical fastening that will not loosen even with sustained jarring movements.

In contrast to a Velcro fastener, this quickly releasable connection is characterised by high shear strength. The self-adhesive backing adheres immediately with excellent final tack, even at high temperatures and on rough surfaces. FELT = Synthetic fleece fibres (grey) very robust long-lasting stable felt, lint-free. PRESSURE SEAL = over 1,000 sealing cycles, material polyolefin, colour black, adhesive acrylate (VHB), temperature resistance continuous -30 to +70°C (short term +95°C), foodstuff resistant, moisture resistant, UV resistant, ageing resistant, chemical and plasticizer resistant, dynamic tensile strength

approx. 21 N/cm², max. static tensile strength and shear strength approx. 160 g/cm², flammability test according to F.A.R. 25.853 (b-2) passed. Storage unprocessed 12 months shelf life at 20°C storage temperature and 50% relative humidity. Dual Lock is a patented pressure lock system from 3M (certified to ISO 9002).

- Quick-change vice jaws suitable for 9-205-K with jaw width 50 mm
- flexible pressure lock, connection for re-release
- firm, stable, precise and accurate connection
- for clamping parts with scratch-sensitive surfaces
- FELT = Synthetic fleece fibres (grey) very robust long-lasting stable felt, lint-free
- Felt grey
- Packing unit pair
- extra accessories Article: KLETT-K050x25##

Dual Lock pressure lock, self-adhesive 50x25mm (VE10)

- approx. dimensions 50 x 25 x 7.5 mm
- weight 6 g

Item no.	WL63661
Manufacturer	BERNSTEIN
Manufacturer article no.	9-900-K50-FILZ
GPSR manufacturer data	BERNSTEIN Werkzeugfabrik Industriehof Trecknase 1 DE-42897 Remscheid www.bernstein-werkzeuge.de
Sales unit	1 pair
Content unit	1 pair
ESD compliant	no