

Extractor LAS 200.1 MD.20 for laser smoke, 230m³/h at 1,000 Pa



- Application fields: Laser engraving, laser marking, laser welding, laser structuring, laser melting etc.
- Mobile extraction system with equipment rolls
- Multi-stage filter for high filtration performance
- Easy handling due to modular design
- Extremely quiet operation
- Control elements on front side
- Powder-coated, robust housing
- Volume flow control: stepless adjustment of suction power
- Constant vacuum even with several suction points
- Particle filter occupancy: optical signaling at 80% and 100
- Interface: M12 as standard equipment
- Remote I/O

- Connections for extraction arms (Ø 50, 75, 80) for extraction at one to four individual workstations
- Extensive accessory set incl. foot switch, hoses, extraction arm console etc.
- Connected load: 900 Watt (110 - 240V / 10 A / 50/60 Hz)
- Sound level (at 50 - 100%) 47 - 58 db(A)
- EC blower

item number	WL63793
manufacturer	ULT
manufacturer item number	LAS 0200.1-MD.20.50.6030
width	390 mm
height	620 mm
depth	400 mm
order unit	1 piece
content unit	1 piece
nominal volume flow	230 m ³ /h at 1.000 Pa, 130 m ³ /h at 5.000 Pa
vacuum max	9000 Pa
noise level (to)	58 dBA
volume flow max	320 m ³ /h