

ESD safety shoe FLASH 6905 XP BOA ESD, W10, S3, black, grey, size 48



ATLAS® brings together state-of-the-art technologies and the anatomical needs of every wearer. The new INNOFLEX SYSTEM® sees itself as a holistic outsole concept and supports the runner in every phase of movement. From the first to the last contact with the ground, the sole complex is permanently guided by the same, natural line of force, the INNOFLEX LINE. It optimally conducts the forces from the heel to the toe and thus supports the natural line of force progression. Special areas such as the CLOUDZONE in the heel are responsible for the corresponding energy absorption, i.e. cushioning. The large-format tread surfaces, which are equipped with particularly energy-absorbing MPU® material, absorb the energy and return it to the motion sequence in a targeted manner. This guarantees fatigue-free running throughout the entire working day.

With the puncture-resistant XP® technology, ATLAS® offers an innovative system to protect the foot against sharp objects such as nails. A high-tech textile material containing aramid

fibers is used for this purpose. This increased safety is not at the expense of wearing comfort, because the textile is metal-free, extremely light and supports the natural torsion of the foot.

The anatomically shaped steel toe cap protects the foot in the toe area against impact of min. 200 joules and a compressive stress of min. 15 kN, according to EN ISO 20345:2012.

The MPU® overcap offers special protection against abrasion in the toe area, protects the upper leather in this area against premature wear and noticeably increases the service life of the safety shoe.

Especially in everyday working life, with high physical stress, temperature-regulating properties are not only required but expected. The aktiv-X functional lining stands for highest quality, innovative technology and offers the wearer permanent, active moisture regulation. The aktiv-X functional lining has a moisture-regulating effect and ensures that the shoes dry again quickly. It does not stain, is skin-friendly and abrasion-resistant.

Work healthier with the right cushioning. The new 3D cushioning system from ATLAS® enables noticeably gentle and fatigue-free walking. The basis for this outstanding walking comfort is formed by three basic components: Pressure relief. Cushioning. Dynamics. This is ensured by the perfect interplay of a pressure-relieving insole and the lightweight and responsive MPU sole technology.

BOA Fit System

ATLAS® offers a wide range of orthopedic insoles. The articles marked here are suitable for orthopedic insoles according to DGUV regulation 112-191. The marking in the shoe is decisive for this.

item number	WL70321
model	FLASH 6905 XP BOA ESD
manufacturer	ATLAS
manufacturer item number	78000-48
GPSR manufacturer information	ATLAS-Schuhfabrik GmbH & Co.KG Frische Luft 159 DE-44319 Dortmund www.atlasschuhe.de
length with packaging	79 mm
width with packaging	23 mm
height with packaging	12 mm
order unit	1 pair

content unit	1 pair
colour manufacturer	black, grey
Colour	grey, black
protective cap	yes
shoe execution	safety shoe
safety class	S3
shoe sole	MPU INNOFLEX system
Slip resistance	SRC
Puncture resistance	XP metal-free penetration resistance
shoe width	W10 (standard width)
features shoes	<ul style="list-style-type: none"> • MPU INNOFLEX System • XP metal-free penetration resistance • steel toe cap • MPU overcap • active-X functional lining • 3D cushioning system • BOA Fit system • suitable for insoles-DGUV 112-191
material shoes	Sportline upper
shoe size EU	48
ESD safe	yes
Category (PPE Regulation)	Category 2

Other versions

item number	shoe size EU	shoe width
WL70309	36	W10 (standard width)
WL70310	37	W10 (standard width)
WL70311	38	W10 (standard width)
WL70312	39	W10 (standard width)
WL70313	40	W10 (standard width)
WL70314	41	W10 (standard width)
WL70315	42	W10 (standard width)
WL70316	43	W10 (standard width)
WL70317	44	W10 (standard width)
WL70318	45	W10 (standard width)
WL70319	46	W10 (standard width)

WL70320	47	W10 (standard width)
WL70321	48	W10 (standard width)
WL70322	49	W10 (standard width)

