

## System luminaire TANEO TNU 1400/940/D - 23 W / 1500 lm



The TANEO can be described in one sentence "ALL-ROUND TALENT FOR WORKING WITH OPTIMUM LIGHT". It creates optimal working conditions in production, assembly and quality assurance.

System luminaires are suitable for workplace-related lighting of industrial workplaces. Depending on the type and structure of the workplace, the luminaire modules are used individually or in combination.

- Fitting: LED
- Control gear: Electronic transformer
- Connected load: 100-240 V; 50/60 Hz
- Power consumption: approx. 23 W
- Luminaire luminous flux: 1500 lm
- Luminaire luminous efficacy: 65 lm/W
- Light color: Neutral white, approx. 4000 K
- Color rendering (Ra):  $\geq 90$
- Protection class: IP 20
- Protection class: I with plug-in power supply unit; III without plug-in power supply unit
- Technology: Infinitely dimmable
- Operation: Multifunction pushbutton
- Luminaire housing
- Material: Aluminum profile
- Surface: Anodized
- Color: Aluminum colors (colorless anodized)
- Lamp cover: Acrylic (PMMA), Structured
- Weight (net): approx. 1.4 kg
- Power cord: 4.70 m power plug CEE 7/VII
- Design: Surface mounted version
- mounting: Screw-on bracket (horizontal)
- glare control: cone prism diaphragm
- Special features: Fixed connection

<b>Item no.</b>	<b>WL70580</b>
Manufacturer	WALDMANN
Manufacturer article no.	114460000-00811087
GPSR manufacturer data	WALDMANN Lichttechnik Peter-Henlein-Straße 5 DE-78056 Villingen-Schwenningen www.waldmann.com
Sales unit	1 piece
Content unit	1 piece
Colour	silver
Material	aluminum
Incl. battery	no
Light source	LED
Lamp or magnifying glass type	system light
Luminous flux	1500 lm
Protection class	IP 20
Connection values	100-240 V; 50/60 Hz
Dimmable	yes
Colour temperature	4000 °K
Power	23 W
ESD compliant	no