

Precision side cutters ESD, XS, Ultra Flush



- Precision side cutters with tapered, flattened head, 80 series
- ESD-safe handles made of synthetic material with opening spring
- Cutting forms: Micro-bevel (with bevel), flush (small bevel) & ultra-flush (without bevel).
- Cutting capacity specification refers to copper
- Suitable for cutting copper wires
- Material: high performance steel alloy
- Phosphated
- Precision ground cutting edges for extra long life and a clean cut
- Induction hardened cutting edges with a high degree of hardness (63-65 HRC)
- Friction-reducing screw connection for smooth cuts without overlapping of the legs
- Ideal for working in hard-to-reach places or for finishing work

Item no.	WL70870
Manufacturer	LINDSTRÖM
Manufacturer article no.	8138
GPSR manufacturer data	SNA Europe SAS/ LINDSTRÖM Antigua Carretera Altube km 5.5 ES-01006 Vitoria-Gasteiz

Products for the electronic industry



	www.lindstromtools.com
Length	270 mm
Width	180 mm
Height	90 mm
Sales unit	1 piece
Content unit	1 piece
Incl. battery	no
ESD compliant	yes
Side cutter cutting capacity	0,1 - 0,5 mm
Cutting edge type	without bevel
Jaw shape	pointed
Tool length	108 mm
Type of side cutters	side cutter

Other versions

Item no.	Side cutter cutting capacity	Cutting edge type	Jaw shape
WL70870	0,1 - 0,5 mm	without bevel	pointed
WL16016	0,1 - 0,6 mm	with fine bevel	pointed
WL15994	0,1 - 0,8 mm	without bevel	oval
WL16014	0,1 - 0,8 mm	without bevel	sharpened to a point
WL15992	0,1 - 1 mm	with fine bevel	oval
WL16012	0,1 - 1 mm	with fine bevel	sharpened to a point
WL16002	0,1 - 1 mm	without bevel	oval
WL16008	0,1 - 1 mm	without bevel	pointed
WL16000	0,1 - 1,25 mm	with fine bevel	oval
WL16023	0,1 - 1,25 mm	without bevel	oval
WL15990	0,2 - 1 mm	with bevel	oval
WL16010	0,2 - 1 mm	with bevel	sharpened to a point
WL16031	0,2 - 1 mm	without bevel	sharpened to a point
WL16020	0,2 - 1,6 mm	with fine bevel	oval
WL16027	0,2 - 1,6 mm	with fine bevel	pointed
WL16006	0,2 - 1,25 mm	with fine bevel	pointed
WL16030	0,2 - 1,25 mm	with fine bevel	sharpened to a point

WL15997	0,2 - 1,25 mm	with bevel	oval
WL16004	0,2 - 1,25 mm	with bevel	pointed
WL20703	0,2 - 1,25 mm	without bevel	pointed
WL70872	0,3 - 1,5 mm	with fine bevel	pointed
WL16018	0,3 - 1,6 mm	with bevel	oval
WL16025	0,3 - 1,6 mm	with bevel	pointed
WL16036	0,3 - 1,6 mm	without bevel	oval
WL16041	0,3 - 1,6 mm	without bevel	pointed
WL20704	0,3 - 1,25 mm	with bevel	sharpened to a point
WL70873	0,3 - 1,25 mm	without bevel	pointed
WL16034	0,3 - 2 mm	with fine bevel	oval
WL16040	0,3 - 2 mm	with fine bevel	pointed
WL70871	0,4 - 1,5 mm	with bevel	pointed
WL16032	0,4 - 2 mm	with bevel	oval
WL16037	0,4 - 2 mm	with bevel	pointed
WL20702	0,5 mm	with cutting edge and bevel	oval