

Precision side cutters ESD with oval head, M, Micro Bevel



- Precision side cutters HS-series
- Soft ESD-safe foam handles with opening spring
- Cutting forms: Micro-bevel (with bevel), flush (small bevel) & ultra-flush (without bevel).
- Cutting capacity specification refers to copper
- Suitable for cutting copper wires
- Material: high performance steel alloy
- Phosphated
- Precision ground cutting edges for extra long life and a clean cut
- Induction hardened cutting edges with a high degree of hardness (63-65 HRC)
- Friction-reducing screw connection for smooth cuts without overlapping of the legs
- Ideal for working on cable harnesses and printed circuit boards

Item no.	WL70918
Model	HS81xx oval
Manufacturer	LINDSTRÖM
Manufacturer article no.	HS 8150
GPSR manufacturer data	SNA Europe SAS/ LINDSTRÖM Antigua Carretera Altube km 5.5

Products for the electronic industry



ES-01006 Vitoria-Gasteiz
www.lindstromtools.com

Length	111 mm
Width	100 mm
Height	12 mm
Sales unit	1 piece
Content unit	1 piece
Head width	12.5 mm
ESD compliant	yes
Side cutter cutting capacity	0,3 - 1,6 mm
Cutting edge type	with bevel
Jaw shape	oval
Tool length	144.8 mm
Type of side cutters	side cutter

Other versions

Item no.	Side cutter cutting capacity	Head width	Cutting edge type	Jaw shape
WL70897	0,1 - 0,8 mm	8 mm	without bevel	oval
WL70917	0,1 - 1,0 mm	10 mm	without bevel	oval
WL70896	0,1 - 1,25 mm	8 mm	with fine bevel	oval
WL70899	0,1 - 1,25 mm	10 mm	with fine bevel	oval
WL70900	0,1 - 1,25 mm	12.5 mm	without bevel	oval
WL70919	0,2 - 1,6 mm	12.5 mm	with fine bevel	oval
WL70895	0,2 - 1,25 mm	8 mm	with bevel	oval
WL70898	0,2 - 1,25 mm	10 mm	with bevel	oval
WL70918	0,3 - 1,6 mm	12.5 mm	with bevel	oval
WL70920	0,3 - 2 mm	16 mm	with fine bevel	oval
WL70921	0,3 - 2 mm	16 mm	without bevel	oval