

## flexible tube light ABLTLE 1 - 3,5 W / 160 lm

---



ABL is small and handy due to its minimal design. You can compare it with a mini flashlight, which can be used everywhere and versatile.

The resistant flexible tube of our flexible tube lights allows highest flexibility, so that the light is always exactly where it is actually needed. In this way, optimal and energy-efficient lighting for the various activities at the industrial workplace or at the machine is quickly and easily adjusted individually. Our articulated head luminaires are particularly suitable for error-free, safe setting and maintenance work. The direct and punctual light can be individually positioned within the processing area.

- Fitting: LED
- Control gear: Electronic ballast in housing
- Connected load: 110-230 V; 50/60 Hz
- Power consumption: approx. 3.5 W
- Luminaire luminous flux: 160 lm
- Luminaire luminous efficacy: 45 lm/W
- Light distribution: Wide beam direct

- Light color: Daylight white, approx. 6500 K
- Color rendering (Ra):  $\geq 75$
- Protection class: IP 20
- Protection class: II
- Operation: External
- Luminaire housing
- Material: Aluminum
- Surface: Anodized
- Lamp cover: Borosilicate
- Lamp frame:
- Color: Black
- Weight (net): approx. 1.1 kg
- Power cord: 3.30 m power plug CEE 7/XVI
- Mounting: base, table clamp (accessories), wall bracket (accessories)
- glare control: without
- Special features: Flood

item number	<b>WL70949</b>
manufacturer	WALDMANN
manufacturer item number	112426001-00074155
GPSR manufacturer information	WALDMANN Lichttechnik Peter-Henlein-Straße 5 DE-78056 Villingen-Schwenningen www.waldmann.com
order unit	1 piece
content unit	1 piece
Colour	black
material	aluminum
Lamp or magnifier type	Flexible tube light
luminous flux	160 lm
Protection class	IP 21
connections	110-230 V; 50/60 Hz
dimnable	no
colour temperature	6501 °K
power	3.5 W
equipping	LED
attachment	Table clamp
ESD safe	no