

2-Tool Rework Station, Desoldering station



DMU Control Unit manages up to 4 tools simultaneously and is fully compatible with 10 different JBC tools.

MSE Electric Desoldering Module is indispensable for a Repairing process.

It provides the best soldering quality thanks to JBC Most Efficient Soldering System and additionally Sleep & Hibernation Modes help to extend life of tips.

It features all the Excellence range benefits such as station customization, full control of soldering processes and remote work management.

DMS works simultaneously with DR560 Desoldering Iron and T245 General Purpose Handle.

- Selectable Temperature: 90 to 450 °C / 190 to 840 °F
- Vacuum: 75% / 570 mmHg / 22.4 inHg

Products for the electronic industry



- Flow rate: 9 SLPM
- USB-B (rear): Software PC / Traceability
- USB-A (front): Firmware update. Soldering Graphics / Profiles management. Dino-Lite USB microscope connection. Compatible models: AM2011 and AM2111.
- Robot: RS-232 remote control or Smart Fume Extractor connection
- LAN: Remote control / Traceability
- Equipotential bonding: Optional connection to EPA
- ESD safe
- Tip to ground resistance: <2 ohms
- Tip to ground voltage: <2 mV RMS
- Peak power: 160 W per tool – 23.5 V
- Operating temp. range: 10 to 50 °C / 50 to 120 °F
- Premium Stations: 232 x 148 x 120 mm / 10.05 kg.
- Package: 525 x 318 x 347 mm / 11.11 kg.

item number	WL71465
model line	Premium Line
manufacturer	JBC
manufacturer item number	DMSE-2QB
length with packaging	525 mm
width with packaging	318 mm
height with packaging	347 mm
order unit	1 set
content unit	1 set
power	160 W
voltage	230 V
temperature range °C	90 – 450 °C
station type	desoldering station, rework station
ESD safe	yes