

## Electrician's scissors, angled, ferrules from 0.5 - 6 mm<sup>2</sup> and 10 - 25 mm<sup>2</sup>, sales packaging

---



Precision ground with fine serration for a clean, slip-free cut. Adapted to the human hand: angled cutting edge and optimized handle design for improved ergonomics. With crimping points for wire end ferrules from 0.5 - 6 mm<sup>2</sup> and 10 - 25 mm<sup>2</sup>. Suitable for cutting the following cables: - 1 x 25 mm<sup>2</sup> such as H01 N2-D flexible / fine-core rubber connecting and control cable for arc welding - 5 x 2.5 mm<sup>2</sup> such as H07 RN-F flexible and fine-core heavy rubber hose cable - Flexible and fine-core cables, single or multi-core up to Ø 15 mm - 5 x 1.5 mm<sup>2</sup> such as damp room cable NYM-J sheathed cable. With opening spring, lockable for transport. With fastening eyelet for attaching a guardrail. Cutting edges made of stainless steel, cutting edge hardness 56 HRC.

item number

WL71711

model

95 05 20 SB

---

Products for the electronic industry



manufacturer	KNIPEX
manufacturer item number	95 05 20 SB
GPSR manufacturer information	KNIPEX-Werk Oberkamper Strasse 13 DE-42349 Wuppertal-Cronenberg www.knipex.de
length	168 mm
width	76 mm
height	21 mm
length with packaging	201 mm
width with packaging	101 mm
height with packaging	20 mm
order unit	1 piece
content unit	1 piece
type of packaging	blister packaging
ESD safe	no
Sheathing handle	with multi-component sleeves