

## High-Precision Hot Air Control Unit, JNAU

---



---

This control unit operates with NH High-Precision Heater Hose Set for soldering or desoldering processes using hot air and T260 Pick & Place Handle for easily place and remove SMDs.

JBC Exclusive System enables the regulation of temperatures and air at very low levels in order to avoid heating adjoining components.

The USB connector allows you to update software and manage parameters from a PC.

For a basic working system, you need at least 1 stand, 1 tool and 1 heating element.

- 230 V
- Nominal power: 70W
- Selectable Temperature: 150 to 450 °C / 300 to 840 °F
- Air flow regulation: 0.15 - 2.5 SLPM
- Vacuum: 53% / 397 mmHg / 15.6 inHg

- ESD safe: Meet ANSI / ESD S20.20-2021
- Equipotential bonding
- Optional connection to EPA: USB-B
- Software PC: USB-A
- Firmware update / Soldering Graphics / Profiles management
- RJ12 Connector
- RS-232 remote control or FAE Fume Extractor connection
- Pedal Connector: Optional tool control

#### • DIMENSIONS AND WEIGHT

- Control Unit:
  - 180 x 170 x 110 mm / 2.83 kg.
  - 7.09 x 6.69 x 4.33 in / 6.23 lb.
- Package:
  - 370 x 370 x 200 mm / 4.20 kg.
  - 14.57 x 14.57 x 7.87 in / 9.26 lb.

<b>Item no.</b>	<b>WL71748</b>
Manufacturer	JBC
Manufacturer article no.	JNASE-2UA
GPSR manufacturer data	JBC Soldering SL Ramón y Cajal 3 ES-08750 Molins De Rei www.jbctools.com
Length	370 mm
Width	370 mm
Height	200 mm
Length with packaging	370 mm
Width with packaging	370 mm
Height with packaging	200 mm
Sales unit	1 piece
Content unit	1 piece
Incl. battery	no
ESD compliant	yes