

## Rod luminaire TANEO TND 1400/940/D - 23 W / 1400 lm

The TANEO can be described in one sentence "ALL-ROUND TALENT FOR WORKING WITH OPTIMUM LIGHT". It creates optimal working conditions in production, assembly and quality assurance.

Linkage luminaires provide large-area, bright and, above all, precisely adjustable lighting in machines, workshops, laboratories and assembly workplaces.

- Mounting: LED
- Control gear: Electronic transformer
- Connected load: 100-240 V; 50/60 Hz
- Power consumption: approx. 23 W
- Luminaire luminous flux: 1500 lm
- Luminaire luminous efficacy: 65 lm/W
- Light color: Neutral white, approx. 4000 K
- Color rendering (Ra):  $\geq 90$
- Color tolerance: 3 SDCM
- Protection class: IP 20
- Protection class: I with plug-in power supply; III without plug-in power supply
- Operation: multifunctional pushbutton
- Luminaire housing
- Color: Aluminum colors (colorless anodized)
- Lamp cover: plastic, structured
- Luminaire frame
- Color: Silver metallic
- Weight (net): approx. 1.9 kg
- Power cord: 3.40 m power plug CEE 7/VII
- Mounting: base, table clamp (accessory), spigot16

<b>Item no.</b>	<b>WL71848</b>
Manufacturer	WALDMANN
Manufacturer article no.	113735000-00809728
GPSR manufacturer data	WALDMANN Lichttechnik Peter-Henlein-Straße 5 DE-78056 Villingen-Schwenningen www.waldmann.com
Sales unit	1 piece
Content unit	1 piece
Colour	black, silver
Material	aluminum
Illuminance range	819-1743 lx

Lamp or magnifying glass type	LED light
Luminous flux	1650 lm
Protection class	IP 67
Connection values	18-30 V; DC
Dimmable	no
Colour temperature	5000 °K
Power	18 W
Equipping	LED
ESD compliant	no

