

Interchangeable blade slot for torque screwdriver with longitudinal handle 1,5mm (26227)



Increases your efficiency: very slim blade geometry especially well suited for hard-to-reach applications.

Application: For controlled screwing at specified torque.

Blade: High quality chrome vanadium molybdenum steel, through hardened, matt chrome plated.

Blade: Wiha ChromTop® blade tip guarantees maximum dimensional stability.

Blade: Color-coded grey.

Blade tip DIN ISO 2380-1.

- Blade thickness 1: 0.25 mm
- Blister packaging: No
- ESD Article: No
- Slot 1: 1.5 mm
- Torque value max (Nm): 0.15 Nm
- diameter hexagonal blade (mm): 4 mm
- Total length (mm): 175 mm
- Length blade visible: 42 mm
- with battery: No

| | |
|--------------------------|---|
| Item no. | WL71988 |
| Alternative article name | 2859015 |
| Manufacturer | WIHA |
| Manufacturer article no. | 26227 |
| GPSR manufacturer data | Wiha Werkzeuge GmbH Obertalstraße 3-7 DE-78136 Schonach www.wiha.com |
| Length | 194 mm |
| Width | 35 mm |
| Sales unit | 1 piece |
| Content unit | 1 piece |

| | |
|----------------------|---------------------------|
| Incl. battery | no |
| Standards | Blade tip DIN ISO 2380-1. |
| Product series | 28590 |
| VDE | no |
| Screw type | slot |
| ESD compliant | no |
| Packaging dimensions | piece |
| Torque (max.) | 0.15 Nm |
| Blade width | 1.5 mm |
| Cutting thickness | 0.25 mm |

Other versions

| Item no. | Blade width | Torque (max.) |
|----------------|---------------|----------------|
| WL71988 | 1.5 mm | 0.15 Nm |
| WL71989 | 2 mm | 0.4 Nm |
| WL71990 | 2.5 mm | 0.4 Nm |
| WL71991 | 3 mm | 0.6 Nm |
| WL71992 | 3.5 mm | 1.1 Nm |
| WL71993 | 4 mm | 2.5 Nm |