

Interchangeable blade slot for torque screwdriver with longitudinal handle 2.0mm (26228)



Increases your efficiency: very slim blade geometry especially well suited for hard-to-reach applications.

Application: For controlled screwing at specified torque.

Blade: High quality chrome vanadium molybdenum steel, through hardened, matt chrome plated.

Blade: Wiha ChromTop® blade tip guarantees maximum dimensional stability.

Blade: Color-coded grey.

Blade tip DIN ISO 2380-1.

- Blade thickness 1: 0.4 mm
- Blister packaging: No
- ESD Article: No
- Slot 1: 2 mm
- torque value max (Nm): 0.4 Nm
- diameter hexagonal blade (mm): 4 mm
- Total length (mm): 175 mm
- Length blade visible: 42 mm
- with battery: No

Item no.	WL71989
Alternative article name	2859020
Manufacturer	WIHA
Manufacturer article no.	26228
GPSR manufacturer data	Wiha Werkzeuge GmbH Obertalstraße 3-7 DE-78136 Schonach www.wiha.com
Length	194 mm
Width	35 mm
Sales unit	1 piece
Content unit	1 piece

Incl. battery	no
Standards	Blade tip DIN ISO 2380-1.
Product series	28590
VDE	no
Screw type	slot
ESD compliant	no
Packaging dimensions	piece
Torque (max.)	0.4 Nm
Blade width	2 mm
Cutting thickness	0.4 mm

Other versions

Item no.	Blade width	Torque (max.)
WL71988	1.5 mm	0.15 Nm
WL71989	2 mm	0.4 Nm
WL71990	2.5 mm	0.4 Nm
WL71991	3 mm	0.6 Nm
WL71992	3.5 mm	1.1 Nm
WL71993	4 mm	2.5 Nm