

L-key Hexagon Ballpoint MagicRing® dull chrome plated 3.0mm (20549)



Application: Lifting screws out of holes or inserting them, especially in hard-to-reach places.

Extra: MagicRing® made of spring steel (from size 3 mm) holds all hexagonal standard screws in any position, regardless of the screw material.

Extra: Spherical head allows screwing at an angle of up to 25°.

Blade: chrome vanadium steel, through hardened, matt chrome plated.

For mechanical applications

In accordance with ISO 2936L.

- Blister packaging: No
- ESD Article: No
- Hexagon socket 1 (mm): 3 mm
- length pin wrench blade (short): 23 mm
- Total length (mm): 128 mm
- with battery: No

Item no.	WL72374
Alternative article name	369R030
Manufacturer	WIHA
Manufacturer article no.	20549
GPSR manufacturer data	Wiha Werkzeuge GmbH Obertalstraße 3-7 DE-78136 Schonach www.wiha.com
Sales unit	1 piece
Content unit	1 piece
Incl. battery	no

Products for the electronic industry



Standards	Based on ISO 2936L.
Product series	369R
VDE	no
ESD compliant	no
Packaging dimensions	piece
Hexagon socket	3 mm
Tool length	128 mm

Other versions

Item no.	Tool length	Hexagon socket
WL72374	128 mm	3 mm
WL72375	142 mm	4 mm
WL72376	163 mm	5 mm
WL72377	184 mm	6 mm
WL72378	206 mm	8 mm
WL72379	231 mm	10 mm