Torque easyTorque adapter electric for slimBits and slimVario® holder in blister 2.8Nm (41344).



Increases your efficiency: 100% compatible with the Wiha slimBit system.
Increases your efficiency: the right torque protects you from material damage and rework.
Reduces your costs: The right torque protects you from warranty claims.
Lowers your costs: Extension to torque tool for LiftUp electric and slimVario® screwdriver sets.
Offers you full protection: each tool individually tested at 10,000 V AC and approved for 1,000 V AC.
Application: For controlled screwing in the area of live parts up to 1,000 V AC, e.g. at the circuit breaker.
Bit holder: Insulated metal bit holder reliably holds all slimBits.
Bit holder: For 6 mm slimBits only.
Accuracy: ±10%.
Controlled screw tightening and at the same time safety in electrical applications is provided by the easyTorque adapter. The torque adapter ensures process-safe application and thus protects against material damage and rework. Furthermore, the insulated easyTorque adapter ensures a secure hold of the 75 mm slimBits and is also compatible with all slimVario products. Thus, the handy adapter transforms both slimVario screwdrivers with bit holder and slimVario Stubby electric as well as the LiftUp electric screwdriver with bit magazine into a torque tool in no time at all. Reaching the torque is audible on the one hand by a click signal and visible on the other hand by the opposite rotation of the yellow ring and the red adapter. The easyTorque adapter is subjected to routine testing in accordance with the international standard IEC 60900 and enables safe working on live parts up to 1,000 V AC.
Bit holders or blades are not included in the scope of delivery.
Tested according to IEC 60900.
• Blister packaging: No
• ESD Item: No

- Torque value fixed (Nm): 2.8 Nm
- Tolerance: 10
- Handle diameter: 5.5 mm
- Total length (mm): 59 mm
- with battery: No

Item no.	**WL72647**
Alternative article name	29701280
Manufacturer	WIHA
Manufacturer article no.	41344
GPSR manufacturer data	Wiha Werkzeuge GmbH Obertalstraße 3-7 DE-78136 Schonach www.wiha.com
Sales unit	1 piece
Content unit	1 piece
Standards	Tested according to IEC 60900.
Product series	2970
VDE	yes
ESD compliant	no
Packaging dimensions	piece
Tool length	59 mm