

Wire end ferrules with plastic collar, 16 mm², DIN (43934), 50 pieces



Increases your process reliability: Consistently high processing quality for lasting contact reliability.

Facilitates handling: Easy and fast cable insertion thanks to funnel sleeve.

Increases your safety: Prevention of cable breakage thanks to protected individual strands.

Increases your safety: high heat resistance of up to 105° C.

Application: Ideally suited for connecting fine-wire conductors, especially for terminal connections.

Particularly when connecting fine-wire conductors in terminals, electricians must ensure that individual wires are not crushed or pushed past. Otherwise, there is a risk of cable breaks or even short circuits, which ultimately represent a potential cause of fire. Wire end ferrules can prevent this and ensure contact reliability and thus long-term operational safety. The conical collar makes it easier to insert the stranded wire into the sleeve during installation. The sleeve also makes it easier to insert the cable into the terminal. Wiha's halogen-free ferrules have a heat resistance of up to 105° C.

For electrical applications

- Blister packaging: No
- ESD Article: No
- Color code DIN: Yes
- Color code FR: No
- color code DE: No
- Content: 50
- Color: blue

- Diameter D1: 5.8 mm
- Diameter D2: 8.8 mm
- Thickness S2: 0.4 mm
- Length L1: 24 mm
- Length L2: 12 mm
- Thickness S1: 0.2 mm
- Nominal size (mm²): 16 mm²
- Stripping range (AWG): 6
- with battery: No

Item no.	WL72767
Alternative article name	C000C160012
Manufacturer	WIHA
Manufacturer article no.	43934
GPSR manufacturer data	Wiha Werkzeuge GmbH Obertalstraße 3-7 DE-78136 Schonach www.wiha.com
Sales unit	1 piece
Content unit	50 piece
Product series	C000C
VDE	no
ESD compliant	no
Packaging dimensions	piece